



Polar-Ply[®] RB-GB

Radiant Barrier – Gable Barrier

Low-Emissivity Radiant Barriers for new and existing residential construction. Provides a cost savings on air conditioning and dramatically increases home comfort levels.

Benefits / Uses: Polar-Ply RB-GB is commonly used as a flame and smoke barrier for single coat stucco systems. This product is a barrier between the systems polystyrene foam assembly and attic or other plenum areas such as fireplace chases where drywall or other noncombustible assemblies do not occur.

Description: Polar-Ply RB-GB is made of high quality aluminum foil laminated to **both sides** of 65 lb. machine glaze kraft paper with a proprietary flame retardant / water resistant adhesive. 500 square foot rolls standard 50" x 120", 68 rolls per pallet, weight 16 lbs per roll, 1,088 lbs. per pallet.

Technical Data:	Basis Weight / MSF:	<u>35 lbs.</u>
	Emissivity:	.03
	Flame Spread:	5
	Smoke Developed:	0

Standards: All Superior products comply with California insulation quality standards, B and P Code §19165, and listed with the Bureau of Home Furnishings and Thermal Insulations. Listing # CA-T032

For further information, see our website at www.polar-ply.com

Manufactured by: Superior Radiant Insulation, Inc.
451 Covina Blvd., San Dimas, CA 91773
Phone: (909) 305-1450 Fax: (909) 305-1448

© Polar-Ply Corp. 2002